

P/N NAS8101-8

Description

NAS8101-8 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| SKU / Model: | NAS81018 |
|-------------------------|---|
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-246-3851 |
| Schedule B: | 7318.15.2000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



^{*} See page 2 for technical characteristics

P/N NAS8101-8 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.408 Inches Minimum And 0.500 Inches Maximum |
| Fastener Length: | 0.470 Inches Minimum And 0.500 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.256 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.087 Inches Minimum And 0.097 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas8101 Professional/industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS8101-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS8101-8 and selecting the quantity you