

# **P/N NAS8101-9**

### **Description**

NAS8101-9 Machine Screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

#### **Additional Information**

SKU / Model:	NAS81019
Minimum Qty (MOQ):	10
NSN:	5305-01-332-7562
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS8101-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.468 Inches Minimum And 0.560 Inches Maximum
Fastener Length:	0.530 Inches Minimum And 0.560 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas8101 Professional/industrial Association Standard

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS8101-9">https://military-fasteners.com/screws/machine+screws/NAS8101-9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/NAS8101-9">https://military-fasteners.com/screws/machine+screws/NAS8101-9</a> and selecting the quantity you