

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS83038
Minimum Qty (MOQ):	130 EA
NSN:	5305-01-482-2898
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS8303-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Maximum
Fastener Length:	0.497 Inches Minimum And 0.500 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.353 Inches Nominal
Head Height:	0.085 Inches Minimum And 0.105 Inches Maximum
Extended Washer Diameter:	0.428 Inches Nominal
Extended Washer Thickness:	0.030 Inches Minimum And 0.037 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416, Tyii, Cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS8303-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.