

# P/N NAS8303-9

## **Description**

Fastener Length: 35/64", Thread: 10-32, Thread Length: 35/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS83039
Minimum Qty (MOQ):	35 EA
NSN:	5305-01-269-7816

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS8303-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.530 Inches Minimum And 0.560 Inches Maximum
Fastener Length:	0.530 Inches Minimum And 0.560 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.353 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.085 Inches Minimum And 0.105 Inches Maximum
Extended Washer Diameter:	0.397 Inches Nominal
Extended Washer Thickness:	0.115 Inches Minimum And 0.142 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 3rd Material
Classification:	Response
Thread Series Designator:	Unjf

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS8303-9">https://military-fasteners.com/screws/machine+screws/NAS8303-9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.