

Description

Fastener Length: 1/2", Thread: 8-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS8402U9
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-568-4843
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS8402U9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Nominal
Fastener Length:	0.562 Inches Nominal
Head Style:	Round Extended Washer
Head Diameter:	0.294 Inches Nominal
Head Height:	0.092 Inches Maximum
Extended Washer Diameter:	0.369 Inches Nominal
Extended Washer Thickness:	0.031 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Navy Codes LHafb110,Ilh38a002
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw,machine,washer Face
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	A286 Per Ams5731 Or Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8402U9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.