

P/N NAS8403-11

Description

Fastener Length: 11/16", Thread: 10-32, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

National Motor Freight:

SKU / Model:	NAS840311
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-322-6100
Schedule B:	7318.15.6080
ECCN:	EAR99

093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS8403-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.598 Inches Minimum And 0.690 Inches Maximum
Fastener Length:	0.660 Inches Minimum And 0.690 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.343 Inches Minimum And 0.363 Inches Maximum
Head Height:	0.085 Inches Minimum And 0.105 Inches Maximum
Extended Washer Diameter:	0.413 Inches Minimum And 0.443 Inches Maximum
Extended Washer Thickness:	0.030 Inches Minimum And 0.037 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas8403 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS8403-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.