

## P/N NAS8403-14

## **Description**

Fastener Length: 7/8", Thread: 10-32, Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS840314
Minimum Qty (MOQ): 5 EA

NSN: 5305-01-322-3602

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS8403-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.788 Inches Minimum And 0.880 Inches Maximum
Fastener Length:	0.850 Inches Minimum And 0.880 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.343 Inches Minimum And 0.363 Inches Maximum
Head Height:	0.085 Inches Minimum And 0.105 Inches Maximum
Extended Washer Diameter:	0.413 Inches Minimum And 0.443 Inches Maximum
Extended Washer Thickness:	0.030 Inches Minimum And 0.037 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas8403 Professional/industrial Association Standard

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS8403-14">https://military-fasteners.com/screws/machine+screws/NAS8403-14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.