

Description

Fastener Length: 1-7/64", Thread: 10-32, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS840318
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-323-4471
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS8403-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.998 Inches Minimum And 1.120 Inches Maximum
Fastener Length:	1.060 Inches Minimum And 1.120 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.343 Inches Minimum And 0.363 Inches Maximum
Head Height:	0.085 Inches Minimum And 0.105 Inches Maximum
Extended Washer Diameter:	0.413 Inches Minimum And 0.443 Inches Maximum
Extended Washer Thickness:	0.030 Inches Minimum And 0.037 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas8403 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS8403-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.