

**Description**

length: 0.385", grip: 0.062", thread: 8-32, reduced head close, tolerance, short thread, philips recess, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS86021
Minimum Qty (MOQ):	20
NSN:	5305-01-525-0806
Schedule B:	7318.15.2095
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



## P/N NAS8602-1 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.370 Inches Minimum And 0.390 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.226 Inches Nominal
<b>Head Height:</b>	0.039 Inches Nominal
<b>Grip Diameter:</b>	0.162 Inches Minimum And 0.163 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	C17 Acft
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Grip Length:</b>	0.052 Inches Minimum And 0.072 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Screw Close Tolerance
<b>Material:</b>	Steel Comp 4340 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS8602-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.