

# P/N NAS8602-2

Military-Fasteners.com

#### Description


length: 0.448", grip: 0.125", thread: 8-32, reduced head, close tolerance, short thread, philips recess, cadmium plated alloy steel, NAS8602 series screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS86022
Minimum Qty (MOQ):	25
NSN:	5305-01-503-8298
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS8602-2 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.433 Inches Minimum And 0.463 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.226 Inches Minimum And 0.257 Inches Maximum
Grip Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Kc135 Gatm A
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

## How to Order

Order this close tolerance screw from our inventory online by visiting <u>https://military-fasteners.com/screws/close+tolerance+screws/NAS8602-2</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.