

P/N NAS8602-8

Description

Fastener Length: 25/32", Thread: 8-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS86028

Minimum Qty (MOQ):

NSN: 5305-01-525-4942

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N NAS8602-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.784 Inches Nominal
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.226 Inches Minimum
Head Height:	0.039 Inches Maximum
Grip Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams-s-5000 Assn Std 1st Material Response Overall Or Ams6415 Assn Std 2nd Material Response Overall Or Ams6322 Assn Std 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas8602 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS8602-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.