



★ FASTENERS

Military-Fasteners.com

P/N NAS8603-1

Description

length: 0.385", grip: 0.062", thread: 10-32, reduced head, short thread, philips recess, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS86031
Minimum Qty (MOQ):	25
NSN:	5305-01-533-4729
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS8603-1 Specifications

Thread Class:	Aal
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.385 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.266 Inches Minimum And 0.303 Inches Maximum
Grip Length:	0.062 Inches Nominal
Thread Quantity Per Inch:	32
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Part Name Assigned By Controlling Agency:	Bolt, 100degree Reduced Head, Phillips Recess, Close Tolerance, Alloy Steel, Short Thread
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall And Ams6322 Assn Std 2nd Material Response Overall And Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas8603 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS8603-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.