

**Description**

length: 0.385", grip: 0.062", thread: 10-32, reduced head, short thread, philips recess, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS86031
Minimum Qty (MOQ):	25
NSN:	5305-01-533-4729
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS8603-1 Specifications

<b>Thread Class:</b>	Aal
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.385 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.266 Inches Minimum And 0.303 Inches Maximum
<b>Grip Length:</b>	0.062 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, 100degree Reduced Head, Phillips Recess, Close Tolerance, Alloy Steel, Short Thread
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-6049 Mil Spec 1st Material Response Overall And Ams6322 Assn Std 2nd Material Response Overall And Mil-s-6049 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty2 Cl2 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas8603 Professional/industrial Association Standard

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS8603-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.