

Description

length: 0.823", grip: 0.50", thread: 10-32, reduced head close tolerance, short thread, philips recess, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS86038
Minimum Qty (MOQ):	50
NSN:	5305-01-445-1326
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS8603-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.573 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.284 Inches Nominal
Grip Diameter:	0.500 Inches Nominal
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.823 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS8603-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.