

Description

length: 0.511", grip: 0.188", thread: 8-32, reduced head close tolerance, short thread, philips recess, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS87023
Minimum Qty (MOQ):	25
NSN:	5306-01-536-2216
ECCN:	EAR99

NAS8702-3



P/N NAS8702-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.511 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.226 Inches Minimum And 0.257 Inches Maximum
Grip Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Point Diameter:	0.1570 Inches Minimum And 0.1595 Inches Maximum
Point Style:	Flat
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.188 Inches Nominal
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Nas4003 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8702-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.