

**Description**

length: 0.511", grip: 0.188", thread: 8-32, reduced head close tolerance, short thread, philips recess, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS87023
Minimum Qty (MOQ):	25
NSN:	5306-01-536-2216
ECCN:	EAR99

NAS8702-3



## P/N NAS8702-3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.511 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.226 Inches Minimum And 0.257 Inches Maximum
<b>Grip Diameter:</b>	0.1630 Inches Minimum And 0.1635 Inches Maximum
<b>Point Diameter:</b>	0.1570 Inches Minimum And 0.1595 Inches Maximum
<b>Point Style:</b>	Flat
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Grip Length:</b>	0.188 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Nas4003 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8702-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.