

Description

length: 0.511", grip: 0.188", thread: 8-32, reduced head close tolerance, short thread, philips recess, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS87023 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5306-01-536-2216 |
| ECCN: | EAR99 |

NAS8702-3



P/N NAS8702-3 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.323 Inches Nominal |
| Fastener Length: | 0.511 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.226 Inches Minimum And 0.257 Inches Maximum |
| Grip Diameter: | 0.1630 Inches Minimum And 0.1635 Inches Maximum |
| Point Diameter: | 0.1570 Inches Minimum And 0.1595 Inches Maximum |
| Point Style: | Flat |
| Nominal Thread Diameter: | 0.164 Inches |
| Grip Length: | 0.188 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Nas4003 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8702-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.