

**Description**

length: 0.448", grip: 0.125", thread: 8-32, reduced head, close tolerance, short thread, philips recess, cadmium plated alloy steel, NAS870 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS8702U2
Minimum Qty (MOQ):	25
NSN:	5305-01-630-7506
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS8702U2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Length:</b>	0.32 Inches Nominal
<b>Fastener Length:</b>	0.424 Inches Nominal
<b>Head Style:</b>	Fillister Countersunk
<b>Head Diameter:</b>	0.226 Inches Minimum And 0.257 Inches Maximum
<b>Head Height:</b>	0.010 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.1640 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>iii Part Name Assigned By Controlling Agency:</b>	Bolt,100 Degree Reduced Head,philips Recess,close Tolerance,a-286,short Thread
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8702U2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.