

Description

length: 0.448", grip: 0.125", thread: 8-32, reduced head, close tolerance, short thread, philips recess, cadmium plated alloy steel, NAS870 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS8702U2
Minimum Qty (MOQ):	25
NSN:	5305-01-630-7506
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS8702U2 Specifications

Thread Class:	3a
Thread Length:	0.32 Inches Nominal
Fastener Length:	0.424 Inches Nominal
Head Style:	Fillister Countersunk
Head Diameter:	0.226 Inches Minimum And 0.257 Inches Maximum
Head Height:	0.010 Inches Maximum
Nominal Thread Diameter:	0.1640 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
iii Part Name Assigned By Controlling Agency:	Bolt,100 Degree Reduced Head,philips Recess,close Tolerance,a-286,short Thread
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unjc

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8702U2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.