

Description

length: 0.511", grip: 0.188", thread: 8-32, reduced head close tolerance bolt, short thread, philips recess, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS8702U3
Minimum Qty (MOQ):	25
NSN:	5306-01-520-4143
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS8702U3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.496 Inches Minimum And 0.526 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.226 Inches Minimum And 0.257 Inches Maximum
Head Height:	0.010 Inches Maximum
Grip Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt, 100 Degrees Reduced Head, Phillips-recess, Close Tolerance, A-286 Short Thread
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjc

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8702U3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.