

P/N NAS8703-13

Military-Fasteners.com

Description

length: 1.135", grip: 0.812", thread: 10-32, reduced head close tolerance bolt, short thread, philips recess, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS870313
Minimum Qty (MOQ):	10
NSN:	5305-01-513-2377
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS8703-13 Specifications

Thread Class:	3a
	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	1.120 Inches Minimum And 1.150 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.266 Inches Minimum And 0.303 Inches Maximum
Grip Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Cross Recess Type lii
End Item Identification:	Ac Wt And Cg Im
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw, Close Tolerance
Special Features:	Cadmium Plated A-286 Cres Screw Shall Be Identified With Green Dye Or Paint On The Thread End . Maximum Coverage May Include The Chamfer Plus One Incomplete Thread.
Color:	Green Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And	
Classification:	Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this close tolerance bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8703-13</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.