

Description

Fastener Length: 1-13/64", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS870314
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-579-4445
Schedule B:	8108.90.3060
ECCN:	EAR99



P/N NAS8703-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	1.183 Inches Minimum And 1.213 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.266 Inches Minimum And 0.303 Inches Maximum
Head Height:	0.049 Inches Nominal
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt, 100 Degree Reduced Head, Phillips Recess, Close Tolerance, A-286, Short Thread
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams Qq-p-416, Type II, Class 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas-8703 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8703-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.