

**Description**

Fastener Length: 1-13/64", Thread: 10-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS870314
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-579-4445
Schedule B:	8108.90.3060
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS8703-14 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	1.183 Inches Minimum And 1.213 Inches Maximum
<b>Head Style:</b>	Fillister Countersunk
<b>Head Diameter:</b>	0.266 Inches Minimum And 0.303 Inches Maximum
<b>Head Height:</b>	0.049 Inches Nominal
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.865 Inches Minimum And 0.885 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, 100 Degree Reduced Head, Phillips Recess, Close Tolerance, A-286, Short Thread
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams Qq-p-416, Type II, Class 2 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas-8703 Professional/Industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8703-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.