

P/N NAS8703-2

Description

length: 0.448", grip: 0.125", thread: 10-32, reduced head, close tolerance, short thread, philips recess, cadmium plated alloy steel, NAS8703 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS87032

Minimum Qty (MOQ): 25

NSN: 5305-01-314-3028

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS8703-2 Specifications

За
Right-hand
0.298 Inches Minimum And 0.348 Inches Maximum
0.433 Inches Minimum And 0.463 Inches Maximum
Flat Countersunk
0.266 Inches Minimum And 0.303 Inches Maximum
0.1885 Inches Minimum And 0.1895 Inches Maximum
Cross Recess Type 1
0.190 Inches
0.115 Inches Minimum And 0.135 Inches Maximum
32
160000 Pounds Per Square Inch
99.0 Degrees Minimum And 101.0 Degrees Maximum
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Green Threads
Iron Alloy 660 Overall
Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Unjc
80205-nas8703 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8703-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.