

Description

Length: 0.573", grip: 0.25", thread: 10-32, reduced head, close tolerance, short thread, philips recess, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS8703U4
Minimum Qty (MOQ):	25
NSN:	5305-01-552-4580
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS8703U4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.558 Inches Minimum And 0.588 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.303 Inches Nominal
Grip Diameter:	0.187 Inches Minimum And 0.188 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unjc

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8703U4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.