

**Description**

Length: 0.573", grip: 0.25", thread: 10-32, reduced head, close tolerance, short thread, philips recess, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS8703U4
Minimum Qty (MOQ):	25
NSN:	5305-01-552-4580
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



## P/N NAS8703U4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.558 Inches Minimum And 0.588 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.303 Inches Nominal
<b>Grip Diameter:</b>	0.187 Inches Minimum And 0.188 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8703U4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.