

# **P/N NAS8704-12**

### **Description**

Fastener Length: 1-", Thread: 1/4-28, Thread Length: "

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

| SKU / Model:       | NAS870412        |
|--------------------|------------------|
| Minimum Qty (MOQ): | 15 EA            |
| NSN:               | 5305-01-583-8388 |
| Schedule B:        | 8108.90.3060     |
| FCCN:              | FARQQ            |



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS8704-12 Specifications**

| Thread Class:                                  | 3a   |
|--|--|
| Thread Direction:                              | Right-hand   |
| Thread Length:                                 | 0.370 Inches Nominal   |
| Fastener Length:                               | 1.120 Inches Nominal   |
| Head Style:                                    | Flat Countersunk   |
| Head Diameter:                                 | 0.397 Inches Nominal   |
| Grip Diameter:                                 | 0.2485 Inches Minimum And 0.2495 Inches Maximum  |
| Point Diameter:                                | 0.241 Inches Minimum And 0.244 Inches Maximum  |
| Single Shear Strength:                         | 95000 Pounds Per Square Inch   |
| Point Style:                                   | Flat   |
| Internal Drive Style:                          | Cross Recess Type Ii   |
| Nominal Thread Diameter:                       | 0.250 Inches   |
| Grip Length:                                   | 0.750 Inches Nominal   |
| Thread Quantity Per Inch:                      | 28   |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch  |
| Countersink Angle:                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| Material:                                      | Iron Alloy 660 Overall   |
| Material Document And Classification:          | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment:                             | Cadmium Overall  |
| Surface Treatment Document And Classification: | Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall                                    |
| Thread Series Designator:                      | Unjc   |

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS8704-12">https://military-fasteners.com/screws/close+tolerance+screws/NAS8704-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.