



Military-Fasteners.com

P/N NAS8704-12

Description

Fastener Length: 1-", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS870412 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-01-583-8388 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N NAS8704-12 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Nominal |
| Fastener Length: | 1.120 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.397 Inches Nominal |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Point Diameter: | 0.241 Inches Minimum And 0.244 Inches Maximum |
| Single Shear Strength: | 95000 Pounds Per Square Inch |
| Point Style: | Flat |
| Internal Drive Style: | Cross Recess Type Ii |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.750 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS8704-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.