

Description

NAS8704-7 Close Tolerance Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS87047
Minimum Qty (MOQ):	10
NSN:	5305-01-612-4758
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS8704-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	0.8075 Inches Nominal
Head Style:	Pan
Head Diameter:	0.355 Inches Minimum And 0.397 Inches Maximum
Head Height:	0.014 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Cross Recess Type li
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.4375 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Special Features:	Close Tolerance
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjc

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS8704-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.