

Description

NAS8704-7 Close Tolerance Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS87047 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-612-4758 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N NAS8704-7 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Nominal |
| Fastener Length: | 0.8075 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.355 Inches Minimum And 0.397 Inches Maximum |
| Head Height: | 0.014 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Single Shear Strength: | 95000 Pounds Per Square Inch |
| Internal Drive Style: | Cross Recess Type Ii |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.4375 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Special Features: | Close Tolerance |
| Material: | Iron Alloy 660 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS8704-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.