

Description

Titanium alloy, flat countersunk head, right hand thread direction, NAS8803 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS8803A2
Minimum Qty (MOQ):	25
NSN:	5305-01-337-8501
Schedule B:	8109.90.0000
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS8803A2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.433 Inches Minimum And 0.463 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.296 Inches Minimum And 0.303 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas8803 Professional/Industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8803A2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.