

Description


titanium alloy, NAS8803 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS8803A5
Minimum Qty (MOQ):	25
NSN:	5305-01-521-2057
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS8803A5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.635 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.266 Inches Minimum And 0.303 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.312 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas8803 Professional/Industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8803A5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.