

**Description**

Titanium alloy bolt, NAS8803 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS8803A7
Minimum Qty (MOQ):	10
NSN:	5305-01-453-4326
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS8803A7 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Minimum
<b>Fastener Length:</b>	0.746 Inches Minimum And 0.776 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.266 Inches Minimum And 0.303 Inches Maximum
<b>Grip Diameter:</b>	0.1879 Inches Minimum And 0.1885 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.428 Inches Minimum And 0.448 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	16000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Nominal And 101.0 Degrees Minimum
<b>Material:</b>	Titanium Alloy Uns R56440 Overall
<b>Material Document And Classification:</b>	Ams4967 Assn Std Single Material Response Overall Or Ams4928 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas8803 Professional/Industrial Association Standard

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8803A7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.