

P/N NAS8803A7

Description

Titanium alloy bolt, NAS8803 series bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS8803A7

Minimum Qty (MOQ): 10

NSN: 5305-01-453-4326

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS8803A7 Specifications

| Thread Class: | 3a |
|---------------------------------------|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.323 Inches Minimum |
| Fastener Length: | 0.746 Inches Minimum And 0.776 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.266 Inches Minimum And 0.303 Inches Maximum |
| Grip Diameter: | 0.1879 Inches Minimum And 0.1885 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 16000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Nominal And 101.0 Degrees Minimum |
| Material: | Titanium Alloy Uns R56440 Overall |
| Material Document And Classification: | Ams4967 Assn Std Single Material Response Overall Or Ams4928 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas8803 Professional/industrial Association Standard |

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS8803A7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.