

Description

NAS9302B-4-02 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[NAS9302B4-02](#)

SKU / Model:	NAS9302B402
Minimum Qty (MOQ):	20
NSN:	5320-01-365-0500
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS9302B-4-02 Specifications

Fastener Length:	0.194 Inches Minimum And 0.254 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.125 Inches Minimum And 0.129 Inches Maximum
Head Major Diameter:	0.206 Inches Minimum And 0.224 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.063 Inches Minimum
Countersink Angle:	99.0 Degrees Minimum And 100.0 Degrees Maximum
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 304 Locking Ringaluminum Alloy 5056 Sleevesteel Comp 8740 Stem
Material Document And Classification:	Ams 5731 Assn Std 1st Material Response Locking Ring Or Ams 5639 Assn Std 2nd Material Response Locking Ringqq-a-430 Fed Spec Single Material Response Sleeveams 6322 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Locking Ringchromate Sleevecadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ringmil-c-5541 Mil Spec Single Treatment Response Sleeveqq-p-416,ty li,cl 2 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas9302 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS9302B-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.