

Description

NAS9302B-5-03 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS9302B503
Minimum Qty (MOQ):	50
NSN:	5320-01-507-6953
ECCN:	EAR99

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS9302B-5-03 Specifications

Head Style:	Countersunk (tubular)
Hole Diameter:	0.125 Inches Nominal
Shank Diameter:	0.156 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Tubular
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 1030 Locking Ring
Material:	Steel Comp 8740 Bolt
Surface Treatment:	Cadmium Bolt And Chromate Bolt

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS9302B-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.