

Description

NAS9302B-5-04 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS9302B504
Minimum Qty (MOQ):	5
NSN:	5320-01-567-8508
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS9302B-5-04 Specifications

Fastener Length:	0.388 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 304 Locking Ring
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Ams 5731 Assn Std 1st Material Response Locking Ring Or Ams 5639 Assn Std 2nd Material Response Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment:	Passivate Locking Ring
Surface Treatment Document And Classification:	Ams 2700 Assn Std Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Ams Qq-p-416,ty li, Cl2 Assn Std Single Treatment Response Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS9302B-5-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.