

**Description**

NAS9302E-4-04 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS9302E404         |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-01-096-7399    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N NAS9302E-4-04 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.319 Inches Minimum And 0.349 Inches Maximum                                  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.125 Inches Minimum And 0.129 Inches Maximum                                  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.229 Inches Maximum   |
| <b>Expansion Device:</b>                              | Plain Stem-type T  |
| <b>Grip Length:</b>                                   | 0.188 Inches Minimum And 0.250 Inches Maximum                                  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                 |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve   |
| <b>Material:</b>                                      | Steel Comp 632 Stem  |
| <b>Material Document And Classification:</b>          | Ams 5657 Assn Std Single Material Response Stem                                |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve                              |
| <b>Surface Treatment:</b>                             | Chromate Sleeve  |
| <b>Surface Treatment:</b>                             | Cadmium Stem   |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Mil Spec Single Treatment Response Sleeve                           |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 1,class 2 Fed Spec Single Treatment Response Stem                |
| <b>Specification/standard Data:</b>                   | 80205-nas9302 Professional/industrial Association Standard                     |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS9302E-4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.