

Description

NAS9305B5-07 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS9305B507
Minimum Qty (MOQ):	10
NSN:	5320-01-515-4529
Schedule B:	8308.20.6000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS9305B5-07 Specifications

Fastener Length:	0.559 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.300 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.375 Inches Minimum And 0.437 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 304 Locking Ring
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams6322 Assn Std Single Material Response Stem
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Locking Ring Or Ams5639 Assn Std 2nd Material Response Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment:	Passivate Locking Ring
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-416, Tyii, CI2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS9305B5-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.