

Description

NAS9307ML-4-02 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS9307ML402
Minimum Qty (MOQ):	10
NSN:	5320-01-588-5478
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS9307ML-4-02 Specifications

Fastener Length:	0.224 Inches Nominal
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Minimum And 0.129 Inches Maximum
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Part Name Assigned By Controlling Agency:	Rivet-blind, Protruding Head, Mechanically Locked Spindle, Bulbed Style A, Class 1, Code M
Special Features:	Sleeve Material Is Monel (nickel-copper Alloy)
Material:	Nickel Alloy Sleeve
Material:	Steel Corrosion Resisting Grip
Material:	Steel Corrosion Resisting Locking Ring
Material Document And Classification:	Ams5737 Assn Std Single Material Response Grip
Material Document And Classification:	Ams5731 Assn Std Single Material Response Locking Ring Or Ams5737 Assn Std Single Material Response Locking Ring
Material Document And Classification:	Qq-n-281 Assn Std Single Material Response Sleeve
Surface Treatment:	Passivate Grip
Surface Treatment:	Passivate Locking Ring
Surface Treatment Document And Classification:	Ams-qq-p-35 Assn Std Single Treatment Response Grip
Surface Treatment Document And Classification:	Ams-qq-p-35 Assn Std Single Treatment Response Locking Ring
Specification/standard Data:	80205-nas9307 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS9307ML-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.