

Description

NAS9308ML-4-02 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS9308ML402
Minimum Qty (MOQ):	20
NSN:	5320-01-217-9135
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS9308ML-4-02 Specifications

Fastener Length:	0.214 Inches Minimum And 0.234 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.125 Inches Minimum And 0.129 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	101.5 Degrees Maximum
Material:	Iron Alloy 660 Locking Ring
Material:	Nickel Alloy 400 Or Nickel Alloy R-405 Sleeve
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Surface Treatment:	Cadmium And Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS9308ML-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.