

**Description**

NAS9308ML-4-02 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS9308ML402                                |
| Minimum Qty (MOQ):      | 20  |
| NSN:                    | 5320-01-217-9135                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS9308ML-4-02 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.214 Inches Minimum And 0.234 Inches Maximum                                  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.125 Inches Minimum And 0.129 Inches Maximum                                  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.229 Inches Maximum   |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.063 Inches Minimum And 0.125 Inches Maximum                                  |
| <b>Countersink Angle:</b>                             | 101.5 Degrees Maximum  |
| <b>Material:</b>                                      | Iron Alloy 660 Locking Ring  |
| <b>Material:</b>                                      | Nickel Alloy 400 Or Nickel Alloy R-405 Sleeve                                  |
| <b>Material:</b>                                      | Steel Comp 632 Stem  |
| <b>Material Document And Classification:</b>          | Ams 5657 Assn Std Single Material Response Stem                                |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Locking Ring                        |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec All Material Responses Sleeve                                |
| <b>Surface Treatment:</b>                             | Cadmium And Chromate Sleeve  |
| <b>Surface Treatment:</b>                             | Cadmium Stem   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Stem                     |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve                   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS9308ML-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.