

P/N NAS9308ML-4-03

Military-Fasteners.com

Description

NAS9308ML-4-03 Blind Rivet

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS9308ML403
Minimum Qty (MOQ):	10
NSN:	5320-01-625-7493
ECCN:	EAR99



P/N NAS9308ML-4-03 Specifications

Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.125 Inches Nominal
Self-plugging Mechanically Locked Stem
0.221 Inches Minimum And 0.229 Inches Maximum
0.257 Inches Minimum And 0.287 Inches Maximum
98.5 Degrees Minimum And 101.5 Degrees Maximum
Iron Alloy 660 Or Nickel Alloy 400 Grip
Iron Alloy 660 Or Steel Comp 304 Locking Ring
Nickel Alloy 400 Sleeve
Steel Comp 632 Or Iron Alloy 660 Stem
Ms5737 Fed Spec Single Material Response Or Qq-n-281 Fed Spec 2nd Material Response Grip
Qq-n-281 Fed Spec Single Material Response Sleeve
Ams5657 Assn Std 1st Material Response Or Ams5737 Assn Std 2nd Material Response Stem
Ams5731 Assn Std 1st Material Response Or Ams5737 Assn Std 1st Material Response Or Ams5639 Assn Std 2nd Material Response Locking Ring
Aluminum Sleeve
Passivate Grip
Passivate Locking Ring
Ams2700, Method 1, Class 4 Assn Std Single Treatment Response Grip
Ams2700, Method 1, Class 4 Assn Std Single Treatment Response Locking Ring
Mil-dtl-83488 Mil Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/NAS9308ML-4-03</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.