

P/N NK4-6A

Military-Fasteners.com

Description

Fastener Length: 13/16", Thread: 1/4-28, Thread Length: 33/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NK46A
Minimum Qty (MOQ):	30 EA
NSN:	5306-00-620-2912
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NK4-6A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.437 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	0.765 Inches Minimum And 0.812 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Locking Feature:	Pellet Threads
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.296 Inches Minimum And 0.328 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Material:	Plastic Polyamide Locking Feature
Material:	Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8630 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Mil-s-6050 Mil Spec 3rd Material Response Fastener Or Mil-s-6098 Mil Spec 4th Material Response Fastener Or Mil-s-6758 Mil Spec 5th Material Response Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NK4-6A</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.