

**Description**

Fastener Length: 1-1/2", Thread: 8-32, Thread Length: 1-1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NK500824
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-104-9496
Schedule B:	3926.90.9995
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NK500-8-24 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.375 Inches Minimum And 1.500 Inches Maximum
<b>Fastener Length:</b>	1.437 Inches Minimum And 1.500 Inches Maximum
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.250 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.106 Inches Minimum And 0.113 Inches Maximum
<b>Locking Feature:</b>	Pellet Threads
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 1010 Overall
<b>Material Document And Classification:</b>	Sae Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NK500-8-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.