

## P/N NK500D5-5

### **Description**

Fastener Length: 21/64", Thread: 5-40, Thread Length: 21/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NK500D55
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-576-2549
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NK500D5-5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.281 Inches Minimum And 0.343 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.343 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.187 Inches Minimum And 0.205 Inches Maximum
Head Height:	0.081 Inches Minimum And 0.088 Inches Maximum
Locking Feature:	Pellet Threads
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.125 Inches
Thread Quantity Per Inch:	40
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NK500D5-5">https://military-fasteners.com/screws/machine+screws/NK500D5-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/NK500D5-5">https://military-fasteners.com/screws/machine+screws/NK500D5-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/NK500D5-5">https://military-fasteners.com/screws/machine+screws/NK500D5-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/NK500D5-5">https://military-fasteners.com/screws/machine+screws/NK500D5-5</a> and selecting the quantity you want then