

**Description**

Fastener Length: 1/2", Thread: 10-24, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NK503108
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-726-6788
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NK503-10-8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.500 Inches Minimum
<b>Fastener Length:</b>	0.500 Inches Nominal
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.292 Inches Minimum And 0.313 Inches Maximum
<b>Head Height:</b>	0.123 Inches Minimum And 0.130 Inches Maximum
<b>Locking Feature:</b>	Pellet Threads
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 8630 Overall Or Steel Comp 4037 Overall
<b>Material Document And Classification:</b>	Mil-s-6050 Mil Spec 1st Material Response Overall Or Ams 6300 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall Or Zinc Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NK503-10-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.