

## P/N NK503-8-10

### **Description**

Fastener Length: 5/8", Thread: 8-32, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NK503810

Minimum Qty (MOQ): 1 EA

NSN: 5305-00-637-8412

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NK503-8-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.562 Inches Minimum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.260 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.108 Inches Minimum And 0.113 Inches Maximum
Locking Feature:	Pellet Threads
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unc

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NK503-8-10">https://military-fasteners.com/screws/machine+screws/NK503-8-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.