

Description

Fastener Length: 5/16", Thread: 6-32, Thread Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NK50565
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-003-8046
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NK505-6-5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.135 Inches Nominal
Fastener Length:	0.280 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.249 Inches Minimum And 0.279 Inches Maximum
Locking Feature:	Pellet Threads
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
iii Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Steel Overall
Material Document And Classification:	Sae Gr 1 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NK505-6-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.