

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 1/2", NK520 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NK520DD10R8
Minimum Qty (MOQ):	5
NSN:	5305-01-016-5513
Schedule B:	7318.15.6080
ECCN:	9A991.d
National Motor Freight:	013680, Alum Screws



* See page 2 for technical characteristics

P/N NK520DD10R8 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Nominal
Fastener Length:	0.500 Inches Nominal
Head Style:	Round
Head Diameter:	0.334 Inches Minimum And 0.359 Inches Maximum
Head Height:	0.137 Inches Maximum
Locking Feature:	Pellet Threads
Internal Drive Style:	Cross Recess Type Ii
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NK520DD10R8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.